







Electric Pumps

PE30, PE40, PE50 Series
- Single Phase



PE50W4N03A

- Meets OSHA regulations for sound (80dBA)
- 2 Stage pumps provide fast run up before the high pressure stage
- Suction strainers screen out contamination to prevent pump damage
- All units are wired as 120 VAC 60 Hz; Optional wiring includes 50 Hz motors and 240 VAC 60 Hz
- 100% Duty Cycle, NEMA 5 Enclosure TEFC motors
- All hand pendants are wired 24 VAC for safety
- Starts under full load


 PE50W4N03A	Use with Cylinder Type	Flow Rate				Motor Size	
		1 st Stage		2 nd Stage			
		in ³ /min	psi	in ³ /min	psi		
Dump Manual Valve w/10 ft. Motor Pendant							
	2W/2P Advance/Return		293	350	18	10,000	0.5 Hp
			311	700	37	10,000	1.0 Hp
			476	700	61	10,000	1.5 Hp
Dump Solenoid Valve w/10 ft. Pendant							
	2W/2P Advance /Return (Auto*)		293	350	18	10,000	0.5 Hp
			311	700	37	10,000	1.0 Hp
			476	700	61	10,000	1.5 Hp
	3W/2P Advance /Return**		293	350	18	10,000	0.5 Hp
			311	700	37	10,000	1.0 Hp
			476	700	61	10,000	1.5 Hp
Manual Valve							
	3W/3P Advance /Hold Return		293	350	18	10,000	0.5 Hp
			311	700	37	10,000	1.0 Hp
			476	700	61	10,000	1.5 Hp
	4W/3P Advance /Hold/Return		293	350	18	10,000	0.5 Hp
			311	700	37	10,000	1.0 Hp
			476	700	61	10,000	1.5 Hp
Manual Valve w/10 ft. Motor Pendant							
	3W/3P Advance /Hold Return		293	350	18	10,000	0.5 Hp
			311	700	37	10,000	1.0 Hp
			476	700	61	10,000	1.5 Hp
	4W/3P Advance /Hold/Return		293	350	18	10,000	0.5 Hp
			311	700	37	10,000	1.0 Hp
			476	700	61	10,000	1.5 Hp
Solenoid Valve w/10 ft. Pendant & Locking Plate							
	3W/3P Advance /Hold Return		293	350	18	10,000	0.5 Hp
			311	700	37	10,000	1.0 Hp
			476	700	61	10,000	1.5 Hp
	4W/3P Advance /Hold/Return		293	350	18	10,000	0.5 Hp
			311	700	37	10,000	1.0 Hp
			476	700	61	10,000	1.5 Hp

1-888-332-6419

www.BVAhydraulics.com

* Advance position holds pressure with motor running or off. Return retracts cylinder with motor off

** Advance position holds pressure with motor running and cylinder Returns when button is released.



Safety Practices

Good industry practice recommends not exceeding 80% of maximum rated capacities of all our products.

Usable Oil Capacity						
1 Gal	2 Gal	3 Gal	5 Gal	10 Gal	15 Gal	25 Gal
Model Number	Model Number	Model Number	Model Number	Model Number	Model Number	Model Number
Dump Manual Valve w/10 ft. Motor Pendant						
PE30DMP01A	PE30DMP02A	PE30DMP03A	-	-	-	-
-	PE40DMP02A	PE40DMP03A	PE40DMP05A	PE40DMP10A	-	-
-	-	PE50DMP03A	PE50DMP05A	PE50DMP10A	PE50DMP15A	PE50DMP25A
Dump Solenoid Valve w/10 ft. Pendant						
PE30H2S01A	PE30H2S02A	PE30H2S03A	-	-	-	-
-	PE40H2S02A	PE40H2S03A	PE40H2S05A	PE40H2S10A	-	-
-	-	PE50H2S03A	PE50H2S05A	PE50H2S10A	PE50H2S15A	PE50H2S25A
PE30DSP01A	PE30DSP02A	PE30DSP03A	-	-	-	-
-	PE40DSP02A	PE40DSP03A	PE40DSP05A	PE40DSP10A	-	-
-	-	PE50DSP03A	PE50DSP05A	PE50DSP10A	PE50DSP15A	PE50DSP25A
Manual Valve						
PE30M3N01A	PE30M3N02A	PE30M3N03A	-	-	-	-
-	PE40M3N02A	PE40M3N03A	PE40M3N05A	PE40M3N10A	PE40M3N15A	PE40M3N25A
-	-	PE50M3N03A	PE50M3N05A	PE50M3N10A	PE50M3N15A	PE50M3N25A
PE30M4N01A	PE30M4N02A	PE30M4N03A	-	-	-	-
-	PE40M4N02A	PE40M4N03A	PE40M4N05A	PE40M4N10A	PE40M4N15A	PE40M4N25A
-	-	PE50M4N03A	PE50M4N05A	PE50M4N10A	PE50M4N15A	PE50M4N25A
Manual Valve w/10 ft. Motor Pendant						
PE30W3N01A	PE30W3N02A	PE30W3N03A	-	-	-	-
-	PE40W3N02A	PE40W3N03A	PE40W3N05A	PE40W3N10A	PE40W3N15A	PE40W3N25A
-	-	PE50W3N03A	PE50W3N05A	PE50W3N10A	PE50W3N15A	PE50W3N25A
PE30W4N01A	PE30W4N02A	PE30W4N03A	-	-	-	-
-	PE40W4N02A	PE40W4N03A	PE40W4N05A	PE40W4N10A	PE40W4N15A	PE40W4N25A
-	-	PE50W4N03A	PE50W4N05A	PE50W4N10A	PE50W4N15A	PE50W4N25A
Solenoid Valve w/10 ft. Pendant & Locking Plate						
PE30S3L01A	PE30S3L02A	PE30S3L03A	-	-	-	-
-	PE40S3L02A	PE40S3L03A	PE40S3L05A	PE40S3L10A	PE40S3L15A	PE40S3L25A
-	-	PE50S3L03A	PE50S3L05A	PE50S3L10A	PE50S3L15A	PE50S3L25A
PE30S4L01A	PE30S4L02A	PE30S4L03A	-	-	-	-
-	PE40S4L02A	PE40S4L03A	PE40S4L05A	PE40S4L10A	PE40S4L15A	PE40S4L25A
-	-	PE50S4L03A	PE50S4L05A	PE50S4L10A	PE50S4L15A	PE50S4L25A

* Advance position holds pressure with motor running or off. Return retracts cylinder with motor off

** Advance position holds pressure with motor running and cylinder Returns when button is released.



Electric Pumps

Electric Power Source



PE50M4N03A



Pump Accessories


See the assortment of accessories designed to work with these pumps.

pg 69



Safety Practices

Good industry practice recommends not exceeding 80% of maximum rated capacities of all our products.



Safety Instructions

Visit our DO'S and DON'TS section to review the best methods of operation. Always be prepared.

pg 92



Pressure Settings


Custom pressure settings available upon request. Contact your local BVA dealer.




Reservoir Sizing

Recommended reservoir sizing is Extended Cylinder + Hose Volume Oil Capacity x 1.3


PE30 Series



PE40/PE50 Series



PE40/PE50 Series With Casters



Reservoir Size	Dimensional Table (in)								Pump Weight by Series* (lbs)		
	A	B	C	D	E	F	G	H	PE30	PE40	PE50
1 Gal	12.7	10.3	19.1	4.7	5.7	12.0	8.1	12.4	61.0	-	-
2 Gal	16.7	12.0	17.9	6.0	6.9	13.2	4.5	12.4	75.0	72.0	-
3 Gal	16.7	12.0	19.7	7.2	8.2	10.5	4.5	12.4	84.0	81.0	91.0
5 Gal	16.7	12.0	24.8	12.3	13.2	15.5	4.5	12.4	-	102.0	112.0
10 Gal	20.9	16.5	31.5	19.0	19.9	22.3	8.3	16.5	-	184.0	194.0
15 Gal	20.9	16.5	34.6	22.1	23.1	25.4	8.3	16.5	-	255.0	265.0
25 Gal	25.6	21.3	34.6	22.1	23.1	25.4	10.6	21.3	-	362.0	372.0

* Pump weights include oil.

1-888-332-6419

www.BVAhydraulics.com

Single Phase Pump Matrix Chart

If you don't see a pump that would fit your application needs, you can custom build a pump to your desired specifications. Use this Pump Matrix Chart as a guide for creating your very own custom built Electric Pump. For assistance in building your pump, call your local BVA Representative.

P **E** **30** **S4L** **02** **A** - **A** **G**

1 **2** **3** **4** **5** **6** **7**
Product Motor Flow Valve Reservoir Voltage Pump
Type Type Group Type/Operation Size Plug Options

1 - Product Type

P Pump

2 - Motor Type

E Induction Electric Motor, TEFC

3 - Flow Group

30 293/18 in3/min @ 350/10,000 psi, 0.5 Hp
40 311/37 in3/min @ 700/10,000 psi, 1.0 Hp
50 476/61 in3/min @ 700/10,000 psi, 1.5 Hp

4 - Valve Type/Operation

CMR Pump Mounted Manifold Block - Pressure & Return Ports Only
WMR CMR Block w/10ft Motor Control Pendant
DMP Dump Valve w/motor pendant 2W/2P
DSP Dump Solenoid Valve w/pendant 3W/2P (Spool Type Valve)
H2S Solenoid Valve 2W/2P - Pendant Control On/Off Only (Poppet Type Valve)
M2N Manual Valve 3W/2P
M3N Manual Valve 3W/3P
M4N Manual Valve 4W/3P
M3L Manual Valve 3W/3P w/Locking Plate
M4L Manual Valve 4W/3P w/Locking Plate
W2N Manual Valve 3W/2P w/10ft Motor Control Pendant
W3N Manual Valve 3W/3P w/10ft Motor Control Pendant
W4N Manual Valve 4W/3P w/10ft Motor Control Pendant
W3L Manual Valve 3W/3P w/Locking Plate and 10ft Motor Control Pendant
W4L Manual Valve 4W/3P w/Locking Plate and 10ft Motor Control Pendant
S3N Solenoid Valve 3W/3P (Spool Type)
S4N Solenoid Valve 4W/3P (Spool Type)
S3L Solenoid Valve 3W/3P w/Locking Plate (Spool Type Valve)
S4L Solenoid Valve 4W/3P w/Locking Plate (Spool Type Valve)

5 - Reservoir Size

01 1 Gallon
02 2 Gallons
03 3 Gallons
05 5 Gallons
10 10 Gallons
15 15 Gallons
25 25 Gallons

6 - Voltage

A 120V 1 ph 60 Hz - US Plug NEMA 5-15P
D 230V 1 ph 50 Hz - European Plug
E 240V 1 ph 60 Hz - No Plug

7 - Pump Options

A External Pressure Adjustment Block (available on any models with 3W/3P or 4W/3P)
G Gauge w/Gauge Adapter 0-15,000 psi 2-1/2" Wet - Installed "A" Port
M Intermittent Motor Option (available on solenoid equipped models only EXCEPT H2S option)
P Pressure Switch (available on solenoid equipped models only)
U Foot Control Switch (available on solenoid equipped models only)
W Wireless Control (available on solenoid equipped models only)



Ordering Example

PE30S4L02A-A

After reviewing this model number, we know that the pump has the following specifications:

- Electric power source
- 1/2 Hp flow group
- Solenoid Valve w/Locking Plate 4W/3P
- 2 gallon reservoir tank
- External Pressure Adjustment Block



PE30S4L02A-A

Related Product: Gauges



Reduce the risk of overloading your product by using a gauge. A variety of graduations and types to suit any need.

pg 69



Safety Instructions

Visit our DO'S and DON'TS section to review the best methods of operation. Always be prepared.

pg 92



Related Product: Hoses

We offer a variety of hoses, fittings, lengths and materials.

pg 72

Not all options are available in all configurations. Table is for reference only. Please consult your local BVA dealer if you want to order a custom pump or if you have questions.